



Compare Products

| | |
|--------------|-------|
| Code | 71380 |
| Model | XJs |



| | |
|-------------|--|
| Note | <p>DRIVE - (ERON D-1 not included) Smartphone connect Dual Speed trigger Fiber Carbon Proplock Propeller Battery Gauge</p> <p>FEATURES 2019</p> <p>Bypass System</p> <p>HD Shaft Seal Carry Handle Cleaning and Lubrication Kit Tow Leash with boltsnap and bungee Extra Bolt snap</p> <p> </p> <p>- Top speed is delivered with fully charged battery - Diver : 70kg weight, 170cm high - drysuit - double 12 tanks - horizontal trim - Conditions : sea water - no flow/current</p> |
|-------------|--|

Dimensions

| | |
|-------------------------------|------------------------------------|
| Use | TECH / COMMERCIALLONG RANGE / CAVE |
| Length | mm 814 (inch 31,1) |
| Width | mm 436 (inch 17,2) |
| Height | mm 340 (inch 13,4) |
| Body diameter | mm 197 (inch 7,8) |
| Weight without battery | kg 14 (lb 30,9) |
| Weight with battery | kg 20 (lb 44,1) |
| Material type | Aluminum body |

Performance

| | |
|-----------------------------------|---------------------------|
| Max static thrust | N 330 (lb 74,2) |
| Top speed | mt/min 85 (ft/min 278) |
| Run time at max speed/drag | min 85 |
| Run time at cruise speed | min 185 |
| Maximum operational depth | mt 200 (ft 656) |
| Test depth | mt 300 (ft 984) |
| Buoyancy/ trim | Neutral Trim and Buoyancy |
| In-water usage temperature | °C -5/+35 (°F +23/+95) |

| Runtime-range | <table border="1"> <thead> <tr> <th>SPEED MT/MIN</th> <th>BURNTIME - MIN</th> <th>RANGE KM (nm)</th> </tr> </thead> <tbody> <tr> <td>FULL TRIGGER</td> <td>85</td> <td>5,9 (2,7)</td> </tr> <tr> <td>60-2KNOTS</td> <td>150</td> <td>7,2 (3,8)</td> </tr> <tr> <td>45-CRUISE</td> <td>185</td> <td>8,1 (4,3)</td> </tr> <tr> <td>30</td> <td>275</td> <td></td> </tr> </tbody> </table> | SPEED MT/MIN | BURNTIME - MIN | RANGE KM (nm) | FULL TRIGGER | 85 | 5,9 (2,7) | 60-2KNOTS | 150 | 7,2 (3,8) | 45-CRUISE | 185 | 8,1 (4,3) | 30 | 275 | |
|---|---|----------------|----------------|---------------|--------------|----|-----------|-----------|-----|-----------|-----------|-----|-----------|----|-----|--|
| | SPEED MT/MIN | BURNTIME - MIN | RANGE KM (nm) | | | | | | | | | | | | | |
| | FULL TRIGGER | 85 | 5,9 (2,7) | | | | | | | | | | | | | |
| | 60-2KNOTS | 150 | 7,2 (3,8) | | | | | | | | | | | | | |
| | 45-CRUISE | 185 | 8,1 (4,3) | | | | | | | | | | | | | |
| 30 | 275 | | | | | | | | | | | | | | | |
| <p>- Top speed is delivered with fully charged battery - Diver : 70kg weight, 170cm high - drysuit - double 12 tanks - horizontal trim - Conditions : sea water - no flow/current</p> | | | | | | | | | | | | | | | | |

| | |
|--------------------------------|-------------------|
| Battery type | |
| Battery type | LI-ion |
| Nominal Voltage | Volt 25,2 |
| Nominal Capacity | Wh 940 |
| Maximum recharging time | h 8 |
| Charger power supply | 90/240 - 50/60 Hz |

| | |
|--------------------------------------|---|
| Features | |
| Smartphone connect | ● |
| External Charge | |
| Suex DRIVe System | ● |
| Battery Gauge | ● |
| Li-ion Battery | ● |
| Fastening device | ● |
| Main Switch | ● |
| Proplock Propeller | ● |
| Speed Adjustment | ● |
| By-pass System | ● |
| Easy Trim | ● |
| Easy Inspect | ● |
| New Handle Design | ● |
| Sealed Motor Compartment | ● |
| NBS - Neutral Buoyancy System | ● |

| | |
|----------------------------|---|
| Made Salt Resistant | ● |
| Motor Protection | ● |
| Battery Protection | ● |
| Certifications | ● |

Features legend:

- : standard
- : optional
- : not available